
Ms Excel All Formulas With Examples

*Ms Excel All
Formulas
With
Examples*

*Downloaded from
www.remodelicious.com
by Mayo & Obrien*

INTRODUCTION: UNLOCKING THE POWER OF EXCEL FORMULAS

Microsoft Excel is more than just a spreadsheet application; it is a powerful tool for data analysis, financial modeling, and business intelligence. At the heart of Excel's functionality lie its formulas—expressions that perform calculations, manipulate text, and derive insights from

raw data. Whether you are a beginner looking to automate simple additions or an advanced user building complex dashboards, mastering **Ms Excel all formulas with examples** is essential for efficiency and accuracy.

Formulas in Excel always begin with an equals sign (=) and can combine cell references, operators, functions, and constants. The real magic happens when you combine multiple functions to solve real-world problems. This

article provides a detailed guide to the most important Excel formulas, each accompanied by practical examples and clear explanations. By the end, you will have a solid foundation to handle data tasks confidently.

CORE MATHEMATICAL AND STATISTICAL FORMULAS

The SUM Formula

One of the most frequently used formulas in Excel is **SUM**. It adds all numbers in a selected range of cells.

Syntax:

`=SUM(number1,
[number2], ...)`

Example: You have

monthly sales in cells A2 to A13. To calculate total sales, enter `=SUM(A2:A13)`. Excel returns the sum of all values in that range. If you have non-adjacent cells (e.g., A2, A5, A9), use `=SUM(A2, A5, A9)`.

The AVERAGE Formula

To find the mean of a dataset, use **AVERAGE**.

Syntax:

`=AVERAGE(number1,
[number2], ...)`

Example: To calculate the average exam score from cells B2 to B30, write `=AVERAGE(B2:B30)`. This formula ignores empty cells and text, making it ideal for

numeric datasets.

The COUNT and COUNTA Formulas

COUNT counts cells containing numbers, while **COUNTA** counts all non-empty cells, including text.

Syntax:

=COUNT(value1, [value2], ...)

Syntax:

=COUNTA(value1, [value2], ...)

Example: In a column of student grades (some blank, some text like "Absent"), **=COUNT**(C2:C50) returns the number of numeric entries.

=COUNTA(C2:C50) returns all filled cells, including "Absent".

The MIN and MAX Formulas

To find the smallest or largest value in a range, use **MIN** and **MAX**.

Syntax:

=MIN(number1, [number2], ...)
=MAX(number1, [number2], ...)

Example: For daily temperatures in D2:D365, **=MIN**(D2:D365) gives the lowest temperature, and **=MAX**(D2:D365) gives the highest.

LOGICAL FORMULAS FOR

DECISION MAKING

The IF Function

The **IF** formula performs a logical test and returns one value if true, another if false. It is the cornerstone of conditional logic in Excel.

Syntax:

```
=IF(logical_test,  
value_if_true,  
value_if_false)
```

Example: Suppose you have sales amounts in column E. To label them as "Target Met" if ≥ 10000 and "Below Target" if not, use `=IF(E2>=10000, "Target Met", "Below Target")`. You can nest IF functions for multiple conditions, but newer alternatives like IFS or

SWITCH are often clearer.

The AND, OR, and NOT Functions

These logical functions combine multiple conditions.

Syntax:

```
=AND(condition1,  
[condition2],  
...)  
=OR(condition1,  
[condition2],  
...)  
=NOT(condition)
```

Example: To check if a student passed both Math (≥ 50) and English (≥ 60), use `=IF(AND(F2>=50, G2>=60), "Pass", "Fail")`. OR returns true if at least one

condition is met.

IFERROR and IFNA

These handle errors gracefully. **IFERROR** catches any error, while **IFNA** specifically catches #N/A errors.

Syntax:

```
=IFERROR(value,  
value_if_error)  
=IFNA(value,  
value_if_na)
```

Example: If you divide A1 by B1 and B1 might be empty, `=IFERROR(A1/B1, "No value")` prevents ugly error messages.

LOOKUP AND REFERENCE FORMULAS

VLOOKUP (Vertical Lookup)

VLOOKUP searches for a value in the first column of a table and returns a value in the same row from a specified column. It is essential for pulling data from large datasets.

Syntax:

```
=VLOOKUP(lookup_v  
alue,  
table_array,  
col_index_num,  
[range_lookup])
```

Example: You have a product list in A2:C100 with Product ID, Name, and Price. To find the price of product with ID "P123", use `=VLOOKUP("P123", A2:C100, 3, FALSE)`. The FALSE

ensures an exact match.

INDEX and MATCH (Advanced Lookup)

Combining **INDEX** and **MATCH** offers more flexibility than VLOOKUP, especially when your lookup column is not the leftmost one.

Syntax:

```
=INDEX(array,
row_num,
[column_num])
=MATCH(lookup_value, lookup_array,
[match_type])
```

Example: To find the price of a product from column C where the

Product Name is in column B and the Price is in column D, use =INDEX(D2:D100, MATCH("Widget", B2:B100, 0)). This is more robust and faster for large datasets.

XLOOKUP (Modern Replacement)

Available in newer Excel versions, **XLOOKUP** simplifies lookups and eliminates many limitations of VLOOKUP and INDEX-MATCH.

Syntax:

```
=XLOOKUP(lookup_value,
lookup_array,
return_array,
[if_not_found],
[match_mode],
```

[search_mode])

Example:

=XLOOKUP("Widget",
B2:B100,
D2:D100, "Not
found") returns the
price directly. No need
to specify column
index number.

TEXT AND STRING FORMULAS

LEFT, RIGHT, and MID

These extract parts of
a text string.

Syntax:

=LEFT(text,
[num_chars])
=RIGHT(text,
[num_chars])
=MID(text,
start_num,
num_chars)

Example: If A1
contains "Excel-2024",

=LEFT(A1,5) returns
"Excel",
=RIGHT(A1,4)
returns "2024", and
=MID(A1,7,4) also
returns "2024".

CONCATENATE and TEXTJOIN

Join text from multiple
cells. **TEXTJOIN** is
newer and offers a
delimiter.

Syntax:

=CONCATENATE(text
1, [text2], ...)
or simply =text1 & "
& text2
=TEXTJOIN(delimit
er, ignore_empty,
text1, [text2],
...)

Example: First name
in B2, last name in C2:
=B2 & " " & C2
gives "John Doe". For a
list: =TEXTJOIN(", "

", TRUE, A1:A10)
combines all non-empty cells with a comma and space.

LEN, TRIM, and UPPER/LOWER

LEN returns the character count, **TRIM** removes extra spaces, and **UPPER/LOWER** change case.

Example: =LEN(A1) counts characters. =TRIM(A1) cleans up messy data. =UPPER(A1) converts to uppercase.

DATE AND TIME FORMULAS

TODAY and NOW

TODAY returns the current date, **NOW** returns date and time. They update automatically.

Syntax: =TODAY()
=NOW()

Example: To calculate age from birthdate in B2: =DATEDIF(B2, TODAY(), "Y").

DATEDIF and EDATE

DATEDIF calculates the difference between two dates in days, months, or years.

EDATE adds months to a date.

Example:

FORMULAS A1, A2, "m") gives full months between two dates. =EDATE(A1, 6) returns the date six months later.

WEEKDAY
and
NETWORKDAYS

WEEKDAY returns the day of the week (1=Sunday, etc.).
NETWORKDAYS counts working days between two dates excluding weekends.

Example:
=NETWORKDAYS(A1, A2) excludes Saturday and Sunday by default.

ROUND,
ROUNDUP,
ROUNDDOWN

These round numbers to a specified number of digits.

Syntax:
=ROUND(number, num_digits)

Example:
=ROUND(3.14159, 2) returns 3.14. For currency, use =ROUND(A1,2) to avoid rounding errors in calculations.

MATH AND TRIGONOMETRY

POWER and Sqrt

FINANCIAL

POWER raises a number to a power; **SQRT** finds square root.

Example: =POWER(5, 3) returns 125.
=SQRT(144) returns 12.

MOD (Modulo)

Returns the remainder after division. Useful for checking even/odd or cyclic patterns.

Example: =MOD(10, 3) returns 1. To check if a number in A1 is even:
=IF(MOD(A1, 2)=0,

"Even", "Odd").

STATISTICAL AND

FORMULAS

SUMIF and SUMIFS

SUMIF adds values based on one condition; **SUMIFS** handles multiple criteria.

Syntax:

=SUMIF(range, criteria, [sum_range])
=SUMIFS(sum_range, criteria_range1, criterial, ...)

Example: