

---

# Simpson Hd 2a Hold Down

---

*Simpson Hd  
2a Hold  
Down*

*Downloaded from  
[www.remodelicious.com](http://www.remodelicious.com)  
by Krista & Esther*

---

## INTRODUCTION TO THE SIMPSON HD2A HOLD DOWN

---

In modern construction, the integrity of a building depends heavily on the connections between its structural components. Whether you are framing a residential home, a commercial structure, or an addition to an existing building, the ability to resist uplift and lateral forces is paramount. High winds, seismic activity, and even routine settling can place

enormous stress on a wood-frame structure. This is where engineered connectors become indispensable. Among the most trusted names in structural connectors, Simpson Strong-Tie offers a range of products designed to provide superior load transfer. One such product, the **Simpson HD2A hold down**, has become a staple for builders, engineers, and contractors who demand reliability and performance. This article explores every aspect of the Simpson HD2A hold down, from its specifications and

installation to its role in modern structural design.

---

## WHAT IS THE SIMPSON HD2A HOLD DOWN?

---

The **Simpson HD2A hold down** is a heavy-duty, pre-engineered connector used to tie wood stud walls to concrete or masonry foundations. It is specifically designed to resist overturning forces caused by wind or seismic events. The HD2A is part of Simpson Strong-Tie's extensive line of hold-down systems, which are critical components in shear wall assemblies. The **Simpson Hd 2a Hold Down** is recognized for its robust construction, ease of installation, and high load capacities. It typically accommodates a 5/8-

inch or 3/4-inch anchor bolt and is available in a variety of finishes, including galvanized and ZMAX, to suit different environmental conditions.

# Key Dimensions and Specifications

Understanding the physical characteristics of the Simpson HD2A is essential for proper specification and installation. The connector is typically manufactured from 10-gauge steel, providing an excellent balance of strength and workability. The overall length of the HD2A is

approximately 14-1/2 inches, with a width of around 3 inches. It features multiple nail holes for attachment to the wood stud, allowing for flexibility in nailing patterns to achieve specific load ratings. The base of the connector includes a slot for the anchor bolt, which is cast into the concrete foundation or attached to a concrete slab. The use of a **Simpson Hd 2a Hold Down** requires careful attention to bolt diameter, embedment depth, and edge distances as specified by the manufacturer and local building codes.

---

### APPLICATIONS AND COMMON USES

---

The **Simpson HD2A hold down** is primarily

used in wood-frame construction where resistance to uplift and overturning is required. This includes a wide range of building types and structural configurations.

## Residential Construction

In residential homes, the HD2A is commonly found in braced wall panels, shear walls, and around large openings such as garage doors. It provides a direct load path from the wall framing to the foundation, ensuring that the structure remains stable under extreme wind loads.

For homes located in hurricane-prone regions or high-wind zones, the **Simpson Hd 2a Hold Down** is often specified in the engineering plans to meet code requirements such as the International Residential Code (IRC) or the Florida Building Code (FBC). Its ability to transfer significant uplift forces makes it an ideal choice for two-story or three-story wood-frame buildings.

## Commercial and Multi-Family

# Structure

## S

Beyond single-family homes, the Simpson HD2A is widely used in commercial and multi-family projects. Apartment buildings, condominiums, schools, and light commercial structures often incorporate shear walls with hold-downs to resist lateral loads. The **Simpson Hd 2a Hold Down** can be installed in both interior and exterior walls, provided that proper corrosion protection is selected for the environment. In seismic zones, such as those found in California, Oregon, and Washington, the HD2A is a critical component in meeting the requirements of the

International Building Code (IBC) and the American Society of Civil Engineers (ASCE) 7 standards.

# Retrofits and Repairs

Existing buildings may also benefit from the installation of Simpson HD2A hold downs. When retrofitting a structure to improve its resistance to earthquakes or high winds, adding hold-downs to existing shear walls can dramatically enhance performance. The **Simpson Hd 2a Hold Down** can be installed in retrofit applications, provided that the existing framing and foundation are capable

of supporting the loads. Simpson Strong-Tie offers specific retrofit solutions and anchoring options, including adhesive anchors and expansion anchors, to accommodate existing concrete conditions.

---

## INSTALLATION GUIDELINES FOR THE SIMPSON HD2A

---

Proper installation of the **Simpson HD2A hold down** is critical to achieving its rated load capacity. Even the best-engineered connector will perform poorly if not installed correctly. The following guidelines reflect Simpson Strong-Tie's official recommendations and industry best practices.

# Required Tools and Materials

Before beginning installation, gather the necessary tools and materials. You will need the Simpson HD2A hold down, the specified anchor bolt (typically 5/8-inch or 3/4-inch diameter), washers and nuts of the appropriate grade, a torque wrench for tightening the anchor bolt, a hammer or pneumatic nailer for attaching nails, and the correct type and quantity of nails as specified in the load tables. It is essential to use Simpson Strong-Tie approved nails, such as 0.148-inch by 3-inch or 0.162-inch by 3-1/2-inch nails, depending

on the load requirement. Using substitute fasteners can void the product's load rating and compromise structural safety.

## Step-by-Step Installation Process

Begin by positioning the Simpson HD2A against the wood stud at the location indicated on the engineering plans. The hold down should be oriented so that the slot aligns with the anchor bolt protruding from the concrete. The base of the connector must sit flush against the concrete or mudsill. Use a level to

ensure the connector is plumb and aligned with the stud. Once positioned, drive the nails into the pre-punched holes in the order recommended by the manufacturer. Typically, this involves filling all nail holes in the body of the connector to achieve the maximum allowable load. For the **Simpson Hd 2a Hold Down**, the nailing pattern is specified in the product literature, and it is important to follow it exactly. After all nails are driven, install the washer and nut on the anchor bolt and tighten to the specified torque. The torque value depends on the bolt diameter and the type of concrete anchor used. Over-tightening can damage the bolt or the concrete, while under-

tightening can reduce load capacity.

## Common Installation Errors to Avoid

Several mistakes can undermine the performance of a Simpson HD2A hold down. One common error is using the wrong size or type of anchor bolt. Always verify the bolt diameter, length, and embedment depth against the approved plans. Another frequent issue is failing to fill all nail holes. While it may be tempting to skip a few nails to save time, doing so reduces the load capacity and may

violate code requirements. Additionally, ensure that the wood stud is of sufficient size and grade. The **Simpson Hd 2a Hold Down** is designed for use with studs that are at least 3x or 4x nominal thickness. Using a 2x stud may not provide enough bearing area to transfer the load without crushing the wood. Finally, check for proper edge and end distances on the concrete. The anchor bolt must be placed far enough from the edge of the concrete to prevent breakout under tension loads.

---

## **LOAD RATINGS AND ENGINEERING DATA**

---

One of the primary reasons engineers and builders choose the Simpson HD2A is its

impressive load rating. The allowable loads for the **Simpson Hd 2a Hold Down** depend on several factors, including the type of fasteners used, the species and grade of the wood, and the size and embedment of the anchor bolt. Simpson Strong-Tie provides comprehensive load tables in their product catalog and on their website. For example, when installed with 0.162-inch by 3-1/2-inch nails and a 5/8-inch diameter anchor bolt embedded 7 inches in 3,000 psi concrete, the HD2A can achieve allowable uplift loads in excess of 7,000 pounds. Higher loads are possible with larger bolts and deeper embedment.

# Factors Affecting Load Capacity

Several variables influence the actual load capacity of a Simpson HD2A hold down in a given installation. Wood species and moisture content affect the withdrawal strength of the nails and the bearing capacity of the stud. Concrete compressive strength and the presence of cracks can influence anchor performance. The **Simpson Hd 2a Hold Down** is tested in accordance with ASTM standards to ensure consistent and reliable performance

across a range of conditions. Engineers should always use the published allowable load values and apply appropriate safety factors as required by the governing building code. When in doubt, Simpson Strong-Tie offers technical support and engineering judgment for complex applications.

---

## **BENEFITS OF USING THE SIMPSON HD2A HOLD DOWN**

---

The **Simpson HD2A hold down** offers several distinct advantages over other hold-down systems. Understanding these benefits helps explain why it is so widely specified in the construction industry.

# High Strength-to-Weight Ratio

## Ease of Installation

### Ratio

Despite being made from relatively lightweight steel, the HD2A delivers impressive load capacity. Its engineered shape distributes stresses efficiently, allowing it to handle heavy uplift and lateral forces without adding excessive weight to the structure. This makes it easier to handle on the jobsite and reduces the overall load on the foundation.

The design of the Simpson HD2A prioritizes ease of use. The pre-punched nail holes are arranged in a logical pattern, and the slot at the base accommodates slight misalignments in the anchor bolt. This reduces the time needed for installation and minimizes the potential for errors. For contractors who value efficiency, the **Simpson Hd 2a Hold Down** is a practical choice.

### Code

# Compliance and Reliability

Simpson Strong-Tie products are widely accepted by building departments across North America. The HD2A hold down is tested and listed in accordance with IBC and IRC requirements, as well as AISI and ASTM standards. Using a product with a proven track record of code compliance gives both the builder and the building official confidence in the structural system. The **Simpson Hd 2a Hold Down** also comes with Simpson Strong-Tie's industry-leading warranty and technical support.

---

## COMPARING THE SIMPSON HD2A WITH OTHER HOLD DOWNS

---

To appreciate what the Simpson HD2A offers, it is helpful to compare it with similar products in the Simpson Strong-Tie lineup.

## Simpson HD2A vs. HD3A

The HD3A is a larger hold down designed for higher load capacities. It has a longer body and accommodates more fasteners, making it suitable for applications where the HD2A is insufficient. However, the HD3A requires more space and larger studs. For many residential and

light commercial applications, the **Simpson Hd 2a Hold Down** provides adequate strength without the added cost and bulk of the HD3A.

## Simpson HD2A vs. HDU Series

The HDU series (such as the HDU2) offers a different design that can be easier to install in tight spaces. The HDU hold downs use a slotted strap that wraps around the stud, often allowing for faster nailing. However, the HD2A typically offers higher allowable loads due to its more robust frame. The choice between

the two depends on the specific load requirements, stud size, and installation preferences. The **Simpson Hd 2a Hold Down** remains a top choice for engineers who need maximum strength in a standard configuration.

---

### CORROSION PROTECTION AND FINISHES

---

Environmental exposure is a critical consideration when selecting any structural connector. The Simpson HD2A is available in different finishes to match the exposure conditions of the project.

## Galvanize

## d Finish

The standard galvanized finish provides adequate corrosion resistance for interior applications and most exterior environments with moderate exposure. It meets the requirements of ASTM A653.

## ZMAX Finish

For projects in highly corrosive environments, such as coastal areas with salt spray or industrial locations with chemical exposure, the ZMAX finish offers superior protection. ZMAX is a hot-dip galvanized coating with additional zinc, providing significantly longer service life than standard galvanizing. When specifying a **Simpson Hd 2a Hold Down** for exterior use or