

---

# Kia Sedona Torque Specs

---

*Kia Sedona Torque Specs*

Downloaded from  
[www.remodelicious.com](http://www.remodelicious.com) by Small &  
Melissa

---

## INTRODUCTION: WHY KIA SEDONA TORQUE SPECS MATTER

---

When you are working on the engine or drivetrain of a Kia Sedona, understanding the precise torque specifications is not just a technical detail—it is a critical step to ensure safety, reliability, and long engine life. The Kia Sedona, a popular minivan known for its spacious interior and smooth ride, has been powered by several engine families over its production years. Each engine requires exact torque values for components such as cylinder head bolts, main bearing caps, connecting rods, and even wheel lug nuts. Using incorrect torque can lead to blown head gaskets, stripped threads, or even catastrophic engine failure. This comprehensive guide covers essential Kia Sedona torque specs for the most common engine configurations, explains why proper torquing is vital, and provides practical tips for DIY mechanics and professional technicians alike.

---

## OVERVIEW OF KIA SEDONA ENGINE OPTIONS

---

To apply the correct torque specs, you first need to know which engine your Kia Sedona has. Over the years, the Sedona (also

known as the Kia Carnival in some markets) has been equipped with several engine variants:

- **3.5L V6 (Lambda II / G6KU)** – used in early to mid-2000s models.
- **3.8L V6 (Lambda II / G6DA)** – introduced around 2006 and used through 2014.
- **3.3L V6 (Lambda II / G6DC)** – found in later generations.
- **2.2L CRDi Diesel (D4HB / R2.2)** – available in some markets for diesel variants.

Most torque specs provided here will focus on the common gasoline V6 engines, but we will also note key differences for the diesel option where applicable. Always verify your specific model year and engine code before starting work.

---

## TORQUE SPECS FOR KIA SEDONA CYLINDER HEAD BOLTS

---

The cylinder head is one of the most torque-critical components. Incorrect tightening can warp the head or cause uneven clamping force, leading to leaks or gasket failure. For the 3.5L and 3.8L V6 engines, head bolts are typically tightened in multiple stages.

## 3.5L V6 (G6KU) Cylinder Head Bolt Torque

1. Step 1: Tighten all bolts to **22 N·m (16 lb-ft)** in the specified sequence.
2. Step 2: Tighten to **44 N·m (32 lb-ft)** following the same order.
3. Step 3: Finally, rotate each bolt an additional **90 degrees** (angle tightening).
4. Final step: Rotate again another **90 degrees** (total 180° after step 2).

**Note:** Some older versions may use a torque-to-yield (TTY) procedure. Always replace head bolts with new ones if they are TTY type.

## 3.8L V6 (G6DA) Cylinder Head Bolt Torque

1. Step 1: Tighten to **20 N·m (15 lb-ft)** in the correct sequence.
2. Step 2: Tighten to **49 N·m (36 lb-ft)**.
3. Step 3: Loosen all bolts completely and then repeat steps 1 and 2.
4. Step 4: Finally, tighten an additional **90 degrees**. Some

service manuals require a second 90-degree turn for certain bolt lengths—check your manual.

## 3.3L V6 (G6DC) Cylinder Head Bolt Torque

Similar to the 3.8L, but with slightly different values:

1. Step 1: **19.6 N·m (14.5 lb-ft)**.
2. Step 2: **44.1 N·m (32.5 lb-ft)**.
3. Step 3: Loosen and repeat steps 1 and 2.
4. Step 4: Final angle tighten of **90 degrees**.

---

### MAIN BEARING CAP TORQUE SPECS

---

The main bearing caps secure the crankshaft and must be torqued precisely to ensure proper clearance and oil film. For the 3.5L and 3.8L engines:

- **3.5L V6:** Main bearing cap bolts: **54 N·m (40 lb-ft)** plus an additional **90 degrees**.
- **3.8L V6:** Main bearing cap bolts: **34 N·m (25 lb-ft)** then **90 degrees**.
- **2.2L CRDi:** Main cap bolts: **49 N·m (36 lb-ft)** then **60 degrees** (verify with diesel manual).

**Important:** Always lubricate bolt threads and under-head surfaces with engine oil before tightening unless specified otherwise.

---

### CONNECTING ROD TORQUE SPECS

---

Connecting rod bolts hold the pistons to the crankshaft. Over-torquing can stretch the bolts; under-torquing can cause rod bearing failure.

- **3.5L V6:** Connecting rod bolts: **20 N·m (15 lb-ft)** then **90 degrees**.
- **3.8L V6:** Connecting rod bolts: **29 N·m (21 lb-ft)** then **90 degrees**.
- **3.3L V6:** Same as 3.8L: **29 N·m + 90°**.
- **2.2L CRDi:** Connecting rod bolts: **29 N·m (21 lb-ft)** then **60 degrees**.

---

### TORQUE SPECS FOR OTHER CRITICAL COMPONENTS

---

## Camshaft Caps and Timing Components

Camshaft bearing cap bolts: typically **9.8-11.8 N·m (87-104 lb-in)**. Use an inch-pound torque wrench for accuracy. Timing chain tensioner bolts: **20 N·m (15 lb-ft)**. Timing cover bolts: **9.8 N·m (87 lb-in)**.

## Oil Pan and Valve Cover Torque

- **Oil pan bolts:** **9.8 N·m (87 lb-in)** for 3.5L; **11 N·m (97 lb-in)** for 3.8L. Tighten in a crisscross pattern.
- **Valve cover bolts:** **9.8 N·m (87 lb-in)** for most V6 engines. Over-tightening can crack the cover.

## Flywheel / Flexplate Bolts

Automatic transmission flexplate bolts: **49 N·m (36 lb-ft)** plus **30-45 degrees** depending on year. Manual transmission flywheel bolts: **88 N·m (65 lb-ft)**.

## Wheel Lug Nuts

Kia Sedona wheel lug nut torque: **90-110 N·m (66-81 lb-ft)**. Always tighten in a star pattern and recheck after 50 miles of driving.

---

### UNDERSTANDING TORQUE SPECIFICATIONS: WHY PRECISION IS CRUCIAL

---

Torque is a measure of rotational force applied to a fastener. Engine components expand and contract with heat, and the clamping force must be sufficient to maintain a seal without exceeding the yield strength of the bolt. Kia Sedona engines use

torque-to-yield (TTY) bolts for many critical fasteners. TTY bolts are designed to stretch permanently during tightening, providing consistent clamping force. However, they can only be used once. Reusing TTY bolts can result in inaccurate clamping and potential failure.

Environmental factors like rust, dirt, and lubricant condition also influence torque readings. Always clean threads and use a drop of oil unless the spec calls for dry torque. When using a torque wrench, apply force smoothly and avoid jerky motions. Calibrate your wrench regularly for accuracy.

### COMMON MISTAKES WHEN TORQUING KIA SEDONA BOLTS

- **Mixing up sequences:** Cylinder head and main bearing cap bolts must be tightened in the exact order specified in the service manual. Skipping or random order can warp components.
- **Using the wrong unit:** Many specs are in N·m, but some older manuals may list lb-ft or lb-in. Double-check conversion.
- **Ignoring angle tightening:** Some DIYers stop after the initial torque value without adding the required angle. This leaves bolts under-tensioned.
- **Not replacing TTY bolts:** Always buy new head bolts for Kia Sedona engines that use torque-to-yield design.

### RECOMMENDED TOOLS FOR TORQUING KIA SEDONA

### COMPONENTS

To achieve accurate torque specs, invest in quality tools:

1. A **beam-style or click-type torque wrench** for N·m and lb-ft ranges (typically 10–150 N·m).
2. An **inch-pound torque wrench** for small bolts like valve covers and oil pans.
3. A **torque angle gauge** or protractor for angle-tightening steps.
4. **Thread chasers and taps** to clean bolt holes before installation.
5. A **digitally calibrated torque adapter** for extra precision on critical joints.

Remember that torque wrenches lose calibration over time. Have them checked annually.

### TORQUE SPECS FOR THE 2.2L CRDI DIESEL (D4HB)

While less common in North America, the diesel Sedona is popular in Europe and Asia. Here are key diesel torque specs:

- **Cylinder head bolts:** Step 1: **30 N·m (22 lb-ft)**; Step 2: **60 N·m (44 lb-ft)**; Step 3: **90 degrees**; Step 4: **90 degrees**.
- **Main bearing caps:** **49 N·m (36 lb-ft) + 60 degrees**.
- **Connecting rods:** **29 N·m (21 lb-ft) + 60 degrees**.
- **Injection pump sprocket bolt:** **88 N·m (65 lb-ft)**.

Diesel engines have higher compression ratios, making precise

torque even more critical to prevent combustion leaks.

---

### **WHERE TO FIND OFFICIAL KIA SEDONA TORQUE DATA**

---

While this article provides reliable general specifications, always cross-reference with a factory service manual (FSM) for your exact model year. Official Kia manuals are available through Kia Techinfo or third-party publishers like Haynes and Chilton. Online forums like KiaSedonaForum.com and carpulse.com also host useful data, but verify with professional sources. If you are unsure about any spec, consult a certified Kia technician.

---

### **CONCLUSION: PROPER TORQUE EQUALS PEACE OF MIND**

---

Whether you are rebuilding a Kia Sedona engine or simply changing the oil pan gasket, paying attention to torque specifications is non-negotiable. The Kia Sedona torque specs for cylinder heads, main bearings, rods, and other fasteners are designed to withstand the stresses of daily driving and long highway trips. By following the correct sequences, using fresh TTY bolts where required, and investing in proper tools, you can avoid costly mistakes and extend